

Please type a plus sign (+) inside this box -



PTO/SB/05 (1/98)
Approved for use through 09/30/2000. OMB 0651-0032
Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

UTILITY PATENT APPLICATION TRANSMITTAL

Attorney Docket No. 2406-5

First Inventor or Application Identifier: Yasuyuki SONODA et al.

Title: DATA TRANSCIEIVING SYSTEM AND METHOD THEREFOR

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Express Mail Label No.

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

ADDRESS TO:

Assistant Commissioner for Patents
Box Patent Application
Washington, DC 20231

1. ☒ Fee Transmittal Form (e.g., PTO/SB/17)
(Submit an original, and a duplicate for fee processing)
2. ☒ Specification Total Pages [94]
(preferred arrangement set forth below)
 - Descriptive title of the Invention
 - Cross References to Related Applications
 - Statement Regarding Fed sponsored R & D
 - Reference to Microfiche Appendix
 - Background of the Invention
 - Brief Summary of the Invention
 - Brief Description of the Drawings (if filed)
 - Detailed Description
 - Claim(s)
 - Abstract of the Disclosure
3. ☒ Drawing(s) (35 USC 113) Total Sheets [27]
4. ☒ Oath or Declaration Total Pages [4]
 - a. ☒ Newly executed (original or copy)
 - b. ☐ Copy from a prior application (37 CFR 1.63(d))
(for continuation/divisional with Box 17 completed)
[Note Box 5 below]
 - i. ☐ **DELETION OF INVENTOR(S)**
Signed statement attached deleting inventor(s) named in the prior application, see 37 CFR 1.63(d)(2) and 1.33(b).
5. ☐ Incorporation By Reference (useable if Box 4b is checked)
The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4b, is considered to be part of the disclosure of the accompanying application and is hereby incorporated by reference therein.

6. ☐ Microfiche Computer Program (Appendix)
7. Nucleotide and/or Amino Acid Sequence Submission
(if applicable, all necessary)
 - a. ☐ Computer Readable Copy
 - b. ☐ Paper Copy (identical to computer copy)
 - c. ☐ Statement verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

8. ☒ Assignment Papers (cover sheet & document(s))
9. ☐ 37 CFR 3.73(b) Statement ☐ Power of Attorney
(when there is an assignee)
10. ☐ English Translation Document (if applicable)
11. ☐ Information Disclosure Statement ☐ Copies of IDS Citations
(IDS)/PTO-1449
12. ☒ Preliminary Amendment
13. ☒ Return Receipt Postcard (MPEP 503)
(Should be specifically itemized)
14. ☐ *Small Entity ☐ Statement filed in prior application, Status still proper and desired
Statement(s) (PTO/SB/09-12)
15. ☒ Certified Copy of Japanese Priority Document
No. 11-103619 Filed: April 12, 1999
16. ☐ Other:

*A new statement is required to be entitled to pay small entity fees, except where one has been filed in a prior application and is being relied upon.

17. If a **CONTINUING APPLICATION**, check appropriate box, and supply the requisite information below and in a preliminary amendment:
☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No. _____
Prior application information: Examiner: _____ Group/Art Unit: _____

18. CORRESPONDENCE ADDRESS

☒ Customer Number or Bar Code Label

Customer No. 22204

or ☐ Correspondence address below

(Insert Customer No. or Attach bar code label here)

Name: Donald R. Studebaker
Firm: NIXON PEABODY LLP
Address: 8180 Greensboro Drive, Suite 800
City: McLean State: VA
Country: U.S.A. Telephone (703) 790-9110

Zip Code: 22102
FAX (703) 883-0370

Name: Donald R. Studebaker

Registration No. 32,815

Signature

Date: April 10, 2000

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

jc525 U.S. PTO
09/545851
04/10/00

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re New PATENT Application of)
Yasuyuki SONODA et al.)
Japanese Priority Application 11-103619) Attn: Applications
Priority Date: April 12, 1999) Branch
For: DATA TRANSCIVING SYSTEM)
AND METHOD THEREFOR) Date: April 10, 2000

PRELIMINARY AMENDMENT

Honorable Assistant Commissioner for Patents
Washington, D.C. 20231

Sir:

Please preliminarily amend the subject application as follows:

IN THE SPECIFICATION:

Page 13, line 3, change "Fig. 28 is an example" to --Figs. 28A, 28B, and 28C are examples--; and

line 5, change "Fig. 29 is an example" to --Figs. 29A, 29B, and 29C are examples--.

TITLE OF THE INVENTION**DATA TRANSCIVING SYSTEM AND METHOD THEREFOR****CROSS REFERENCE TO RELATED APPLICATIONS**

- 5 The disclosure of Japanese Patent Application No. Hei 11-103619 (filed on April 12, 1999), including specification, claims, drawings and abstract is incorporated herein by reference in its entirety.

10 **BACKGROUND OF THE INVENTION**

1. **Field of the Invention**

This invention relates to a data transceiving system, and particularly to retrial transmission.

2. **Description of the Related Art**

- 15 In Japanese Patent Application Laid-Open No. H8-275140/1996 (published) a bidirectional program response apparatus is disclosed for randomly delaying transmission times from the time of a response operation, receiving terminal by receiving terminal, in order to prevent the
- 20 concentration of transmissions of response information to a bidirectional program. Using such an apparatus, the actual times of transmissions from a broadcast receiving party are delayed and dispersed even when response operations are temporarily concentrated for the broadcast.
- 25 Thus it is possible to avoid telephone line blowout between the receiving terminals and the center.

The following problem arises, however, when the time of response information transmission is delay-processed in this manner. In cases where, as a result of a delayed transmission, a telephone connection with the center cannot be made, even though a user believes that a shopping request has been made, a situation will arise where no response information has actually been transmitted to the center.

SUMMARY OF THE INVENTION

10 An object of the present invention is to provide a data transceiving system or method therefor wherewith the problem noted above can be resolved, and, when response information has been transmitted after a delay, the response information receiving equipment can more
15 definitely receive the response information.

Another object of the present invention is to provide a data transceiving system or method therefor wherewith retrials can be made according to the allowed volume on the communication line between the response
20 information receiving equipment and the television receivers.

In accordance with characteristics of the present invention, there is provided a data transceiving system wherein : data are sent from a broadcasting station to a
25 plurality of television receivers by broadcasting;
response information is sent from said television

receivers to response information receiving equipment by communication lines; and said broadcast station makes transmissions inclusive of retrial information to enable said television receivers to make retrial transmissions

5 when said television receivers are unable to establish communications with said response information receiving equipment.

In accordance with characteristics of the present invention, there is provided a data transceiving system wherein: data are sent from a broadcasting station to a plurality of television receivers by broadcasting; response information is sent from said television receivers to response information receiving equipment by communication lines; and said television receivers, upon

10 receiving data containing retrial information to enable retrial transmissions with said response information receiving equipment when communications could not be established with said response information receiving equipment, retransmit said response information on basis

15 of that retrial information.

20

In accordance with characteristics of the present invention, there is provided a data transceiving system comprising: a broadcast unit for broadcasting data; a plurality of television receivers for receiving

25 said data and transmitting response information over communication lines; and response information receiving

equipment, connected via said communication lines to said television receivers, for receiving response information from said television receivers; wherein: said broadcast unit sends retrieval information, according to allowable
5 volume of said communication lines, included in said data; and said television receivers retrieval-transmit said response information on basis of said retrieval information received when communications could not be established with said response information receiving equipment.

10 In accordance with characteristics of the present invention, there is provided a television receiver for receiving data broadcast from a broadcast unit and displaying images, and transmitting response information to response information receiving equipment over
15 communication lines, wherein: said response information is retrieval-transmitted to said response information receiving equipment, on basis of retrieval information received from said broadcast unit, when communications could not be established with said response information
20 receiving equipment.

In accordance with characteristics of the present invention, there is provided a television receiver comprising: means for receiving data sent from a broadcast unit; means for outputting display data based
25 on said received data to display means; and communication means, being means that transmit said response

information over communication lines, for retrieval-transmitting said response information, on basis of retrieval information contained in said received data, when communications could not be established with said
5 response information receiving equipment.

In accordance with characteristics of the present invention, there is provided a television receiver comprising: means for receiving data sent from a broadcast unit; means for displaying display data based
10 on said received data; and communication means, being means that transmit response information over communication lines, for retrieval-transmitting said response information, on basis of retrieval information sent from said broadcast unit, when communications could
15 not be established with response information receiving equipment.

In accordance with characteristics of the present invention, there is provided a data receiver comprising: means for receiving data sent from a broadcast unit; and
20 communication means for sending response information over communication lines; wherein: said communication means retrieval-transmit said response information, based on retrieval information contained in said data received, when communications could not be established with response
25 information receiving equipment.

000740" 15254550

09545351-044000

In accordance with characteristics of the present invention, there is provided a data transceiving system wherein: data are sent from a broadcast station to a plurality of data receivers by broadcasting; response
5 information is sent after a delay from said plurality of data receivers to response information receiving equipment by communication lines; said broadcast station sends retrieval information contained in said data; said data receiver resends said response information based on
10 said retrieval information when communications could not be established with said response information receiving equipment; and said response information receiving equipment, upon receiving said response information from said data receiver, notifies a user of said data receiver
15 that response information was received by a communication line other than said communication lines.

In accordance with characteristics of the present invention, there is provided a television receiver comprising: a tuner for selecting a transport stream from
20 data sent from a broadcast unit; a transport decoder for selecting display data of a desired service from said selected transport stream; an AV decoder for outputting said display data of said selected service to a monitor; a control input unit wherewith a user inputs response
25 information; a line communication unit for sending said response information over a communication line; a CPU;

and a memory in which a control program for said CPU is stored; wherein: said control program retrieval-transmits said response information via said line communication unit, based on retrieval information contained in said data, when communications could not be established with said response information receiving equipment.

In accordance with characteristics of the present invention, there is provided a data transceiving system comprising: a server wherein prescribed data are stored in memory unit; and a plurality of computers capable of being connected to said server; wherein: said server, when said computers send download requests to said server, send data specified by said download requests to said computers; said server, upon receiving said download requests, sends download request transmission-delaying programs to said computers making those download requests; and said computers send download requests, after a delay, to said server, based on said download request transmission-delaying program.

In accordance with characteristics of the present invention, there is provided a data transceiving system server which, being a server connected to a plurality of computers, upon receiving a download request from any computer, does not cause data specified by that download request to be transmitted to said computer making that download request, but rather sends thereto a download

request transmission-delaying program which sends download requests to said server after a delay.

In accordance with characteristics of the present invention, there is provided a data transceiving system comprising: a broadcast unit for broadcasting data: a plurality of data receivers for receiving said data and transmitting response information over communication lines; and response information receiving equipment connected to said data receivers via said communication lines for receiving response information from said data receivers; wherein: said broadcast unit sends probability variation data, included in said data, wherewith probability of generating a transmission time varies over time; and said data receivers determine transmission scheduling times for transmitting to said response information receiving equipment on basis of said received probability variation data.

In accordance with characteristics of the present invention, there is provided a data transceiving system for transmitting data by broadcast from a broadcast station to a plurality of data receivers, and transmitting response information from said data receivers to response information receiving equipment by communication lines, wherein: said receivers, upon receiving probability variation data wherewith the probability wherewith transmission times are generated

varies over time from said broadcast unit, determine transmission scheduling times for transmitting to said response information receiving equipment on basis of said received probability variation data.

5 In accordance with characteristics of the present invention, there is provided a data receiver for receiving data broadcast from a broadcast unit and sending response information over a communication line to response information receiving equipment, wherein:
10 transmission scheduling times for transmitting to said response information receiving equipment are determined on basis of received probability variation data, when said probability variation data, wherewith probability with which transmission times are generated varies over
15 time, are received from said broadcast unit.

In accordance with characteristics of the present invention, there is provided a data transceiving method for receiving broadcast data and sending response information over communication lines, wherein: when data
20 inclusive of retrial information according to allowable volume on said communication lines are received, when communication could not be established using said communication lines, said response information are retrial-transmitted on basis of said received retrial
25 information.

In accordance with characteristics of the present invention, there is provided a data transceiving method for sending response information over communication lines when data broadcast are received, wherein: said data
5 include probability variation data wherewith probability of generating a transmission time varies over time; and transmission scheduling times for transmitting over said communication lines are determined on basis of said received probability variation data.

10 While the novel features of the invention are set forth in a general fashion, both as to organization and content. Other objects and features of the present invention will be more apparent to those skilled in the art on consideration of the accompanying drawings and
15 following specification wherein are disclosed several exemplary embodiments of the invention with the understanding that such variations, modifications and elimination of parts may be made therein as fall within the scope of the appended claims without departing from
20 the spirit of the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a diagram showing how radio signals are sent in satellite broadcasting;

25 Fig. 2 is a diagram representing the configuration of transmitters in satellite broadcasting;

Fig. 3 is a diagram representing a transport stream sent in satellite broadcasting;

Fig. 4 is a diagram of the structure of packeted data;

5 Fig. 5 is a diagram of the content of control data PMT1;

Fig. 6 is a diagram of the content of control data PAT;

10 Fig. 7 is a diagram of the content of control data NIT;

Fig. 8 is a diagram of a common configuration for a receiver unit;

15 Fig. 9 is an overall configuration diagram of a bidirectional transceiving system according to the present invention;

Fig. 10 is a detailed functional block diagram for the receiver shown in Fig. 9;

Fig. 11 is a diagram representing a transmitted transport stream;

20 Fig. 12 is a diagram of the content of control data PMT1;

Fig. 13 is a diagram of the content of control data PAT;

25 Fig. 14 is a diagram of the content of navigation data NVT1;

Fig. 15 is a diagram of the content of navigation data NVT2;

Fig. 16 is a diagram of a hardware configuration in a receiver;

5 Fig. 17 is a detailed diagram of an AV decoder 52;

Fig. 18 is a flowchart for a program in reception processing;

Fig. 19 is a flowchart for a program that interprets and executes navigation data;

10 Fig. 20 is a diagram of an external view of a remote control apparatus 78;

Fig. 21 is a diagram representing a household product television shopping screen displayed on a TV set 46;

15 Fig. 22 is a diagram representing a household product television shopping screen displayed on the TV set 46;

Fig. 23 is a diagram representing an apparel product television shopping screen displayed on the TV set 46;

20 Fig. 24 is a delayed transmission registration information table;

Fig. 25 is a delayed transmission registration processing flowchart;

25 Fig. 26 is a delayed transmission registration processing flowchart;

Fig. 27 is a diagram of the content of a communication log recorded in a memory 60;

Fig. 28 is an example of a probability density function;

5 Fig. 29 is an example of a probability distribution function;

Fig. 30 is a diagram of how still videos are transferred; and

10 Fig. 31 is a diagram for describing another embodiment.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

Table of Contents

	1. Satellite Broadcast System Overview
15	1.1 Radio Signal Transmission in Satellite Broadcasting
	1.2 Transmitter Unit Configuration
	1.3 Transport Stream Structure
	1.4 Receiver Unit Configuration
20	2. Bidirectional Transceiving System 1
	2.1 Overview
	2.2 Detailed Description
	2.3 Transmission Data
	2.4 Concrete Configuration Example for and
25	Operation of Receiver
	2.5 Delayed Transmission Processing

2.6 Cause Detection Processing for Delayed Transmissions

2.7 Computation of Initial Scheduled Transmission Time

3. Other Embodiments

A description is given below of the present invention as applied to satellite broadcasting. If data broadcasting is in view, however, the present invention can be applied to ground wave broadcasting, cable TV and other land line broadcasting, and internet broadcasting, etc. Before describing an embodiment of the present invention, an overview of a satellite broadcasting system is first given.

1. Satellite Broadcasting System Overview

1.1 Radio Signal Transmission in Satellite Broadcasting

In Fig. 1 is represented a model of how radio signals are sent in satellite broadcasting. A radio signal from a ground station 2 is sent via a broadcast satellite 4 back to earth. Multiple transport streams TS1, TS2, and TS3 are sent from the broadcast satellite 4. These transport streams are differentiated by frequency and plane of polarization, etc.

In the transport stream TS1, a plurality of services (corresponding to channels in ground wave broadcasting)

SV11, SV12, SV13, and SV14 are packeted and multiplexed by time division. In transport stream TS2, similarly, services SV21, SV22, SV23, and SV24 are multiplexed, and in transport stream TS3, services SV31, SV32, SV33, and SV34 are multiplexed. In each transport stream, furthermore, in addition to video data and audio data for the services, control data for indicating program information, control data for indicating the current time, and control data that are necessary in connection with packeting, etc., are also sent.

In Fig. 1, three transport streams are represented. In actual practice, however, many more transport streams are sent. In Fig. 1, furthermore, four services are shown multiplexed in each transport stream. In actual practice, however, many more services are multiplexed.

1.2 Transmitter Unit Configuration

In Fig. 2 is represented a configuration for a transmitter unit for generating and transmitting the transport streams described in the foregoing. Only the transport stream TS1 is represented in Fig. 2, but the other transport streams TS2 and TS3 are generated in the same way.

Video/audio data ES11 of the service SV11 are compressed by an encoder E1 and sent to a multiplexer 10. Similarly, video/audio data ES12 of the service SV12 are compressed by an encoder E2 and sent to the multiplexer

10, video/audio data ES13 of the service SV13 are compressed by an encoder E3 and sent to the multiplexer 10, and video/audio data ES14 of the service SV14 are compressed by an encoder E4 and sent to the multiplexer 10.

A control data generator 6 generates control data for packet multiplexing, control data for indicating program information, and control data for indicating the current time. The control data for packet multiplexing are added for such purposes as correctly identifying the video/audio data of the plurality of services time-divided and packeted.

The multiplexer 10 time-divides the control data and the compressed video/audio data ES11, ES12, ES13, and ES14 to form fixed-length packets which it sends as transport stream TS1.

A scrambler 12 scrambles the output packets using a scrambling key provided by a scrambling key controller 16. The scrambled transport stream TS1 is modulated in a modulator 14 and broadcast to viewers via the broadcast satellite 4.

The scrambling key used in the scrambler 12 is encrypted by an ECM generator 8 and rendered into ECM (entitlement control message) data. That is, ECM data are generated that further encrypt a key for undoing the

scrambling. The multiplexer 10 forms packets that include these ECM data.

1.3 Transport Stream Structure

In the transport stream TS1 generated by the transmitter unit diagrammed in Fig. 2 are multiplexed the video data ES(V)1 and audio data ES(A)1 of the service SV11, the video data ES(V)2 and audio data ES(A)2 of the service SV12, the video data ES(V)3 and audio data ES(A)3 of the service SV13, and the video data ES(V)4 and audio data ES(A)4 of the service SV14, as diagrammed in Fig. 3.

Control data NIT, PAT, PMT1, PMT2, PMT3, and PMT4 for packet multiplexing are also multiplexed. These control data can separate the multiplexed video/audio data of the services SV11, SV12, SV13, and SV14.

In addition, control data ECM1, ECM2, ECM3, and ECM4 for scrambling keys, control data EIT1, EIT2, EIT3, and EIT4 for indicating program information, and control data TDT for indicating the current time, etc., are multiplexed. In actual practice, moreover, much more control data are multiplexed (not shown in drawings).

Packeting is performed as indicated by the vertical line 18a in Fig. 18. That is, packeting is performed in the order of control data NIT, PAT, PMT, EIT, TDT, ECM, video data ES(V), and audio data ES(A). When the packeting is completed to the audio data ES(A)4,

packetizing is then repeated beginning with control data NIT (cf. vertical line 18b).

In Fig. 4 is diagrammed the basic structure of packeted data. Both control data and video/audio data are made into packets having the data structure diagrammed in Fig. 4. A PIDentification (hereinafter referred to as PID) is attached at the head of the packeted data. The PID is a code that is uniquely added to each of the packets to identify them. The content data are the data to be packeted (control data, video/audio data, etc.).

In Fig. 5 are diagrammed the data content of the control data PMT1 for packet multiplexing. In PMT1 are written the PID for the video data ES(V)1 and ES(A)1 for the service SV11, and the PID for the ECM1 for unscrambling those data. In PMT2, PMT3, and PMT4 are similarly written PIDs for the services SV12, SV13, and SV14, respectively.

As diagrammed in Fig. 6, in the PAT are written the PID for the PMT1 corresponding to the service SV11, the PID for the PMT2 corresponding to the service SV12, the PID for the PMT3 corresponding to the service SV13, and the PID for the PMT4 corresponding to the service SV14.

As diagrammed in Fig. 7, in the NIT are written such transmission specifications as frequency and plane of polarization for all of the transport streams TS1, TS2,

and TS3, together with lists of services multiplexed in those transport streams. Thus it is possible to know to which transport stream of what frequency a given service has been multiplexed.

5 1.4 Receiver Unit Configuration

An overview of a receiver unit is diagrammed in Fig.

8. A transport stream is selected by a tuner 22, scrambling is undone by a descrambler 24, and video/audio data ES for a desired service are separated by a transport decoder 26. A microprocessor (MPU) 28 sends the ECM obtained to an IC card 30, and a scrambling key restored by the IC card 30 is received. The MPU 28 sets this scrambling key in the descrambler 24. Thus the video/audio data ES can be descrambled.

15 The MPU 28 also sets the PID for the video/audio data ES of the desired service in the transport decoder 26. Thus the transport decoder 26 outputs the video/audio data ES for that service. Also, when the PID of control data are set in the transport decoder 26, the separated control data are sent to the MPU 28.

25 Assuming now that the service SV33 of the transport stream TS3 is being received, the operation is now described for the case where a command to change over to the service SV12 of the transport stream TS1 has been sent to the MPU 28. First, the MPU 28 controls the transport decoder (that is, sets the PID for the control

5 The MPU 28 controls the tuner 8 so that the tuner 8 receives the transport stream TS1. The MPU 28 controls the transport decoder 26, so as to obtain the PAT and PMT2 are fetched. The MPU 28 obtains the PIDs for the video data ES(V)2 and audio data ES(A)2 for the desired
10 service SV12 and the ECM PID.

When a command is sent to the MPU 28 to display the program schedule and program information, the MPU 28 controls the transport decoder 26 so as to fetch the EIT data. The MPU 28 outputs command to display the program information, etc. based on the fetched EIT data.

20

A bidirectional transceiving system 1 that is one embodiment of the present invention is now described.

2.1 Overview

The overall configuration of the bidirectional transceiving system 1 according to this embodiment of the present invention is diagrammed in Fig. 9.

A broadcasting unit 140 broadcasts such digital data as video and audio. When that is being done, retrieval information corresponding to the allowed volume on the communication line between the response information receiving equipment 150 and television receivers 160₁ to 160n are included in these digital data and broadcast.

The television receivers 160₁ to 160n receive the digital data noted above. The television receivers 160₁ to 160n perform display based on the received digital data. When a user views a displayed image, and inputs response information, the television receivers 160₁ to 160n transmit that response information over the communication line to the response information receiving equipment 150.

The response information receiving equipment 150 can be connected by communication lines to the television receivers 160₁ to 160n and thus receive response information from the television receivers.

When communications are not established with the response information receiving equipment 150, the

00010" TSS4550

television receivers 160₁ to 160_n retrieval-transmit the response information on the bases of the retrieval information received from the broadcast unit 140. Thus, even when responses to the response information receiving equipment from the television receivers 160₁ to 160_n are concentrated, retrieval transmissions are made based on the response information corresponding to the allowable volume on the communication lines. Accordingly, response information can be received with greater certainty even when at first no connection could be made with the response information receiving equipment 150. In addition, retrieval transmission processing corresponding to the allowable volume on the communication lines can be controlled by the retrieval information transmitted from the broadcast unit 140.

2.2 Detailed Description

The configuration of the broadcast unit 140 is the same as the broadcast unit diagrammed in Fig. 2 except for the generation of navigation data (described below), and so is not further described here. As diagrammed in Fig. 9, the response information receiving equipment 150 has a communication unit 151, controller 153, and memory unit 155. The communication unit 151 is capable of sending and receiving data between the television receivers 160₁ to 160_n over telephone lines as communication lines. The controller 153 controls the

communication unit 151 and manages data received. The memory unit 155 stores response information received by the communication unit 151.

The television receiver 160₁ is now described with reference to Fig. 10. The television receiver 160₁ has receiving means 161, display data output means 163, input means 165, communication means 167, detection means 171, retrieval condition alteration means 173, memory means 175, edit means 177, and display means 179.

The receiving means 161 receive digital data transmitted from the broadcast unit 140 indicated in Fig. 9. The display data output means 163 output display data based on the digital data received to the display means 179. The display means 179 perform display based on the display data. The user inputs response information to the input means 165 based on that display.

The communication means 167, when communication cannot be made with the response information receiving equipment 150, compute retrieval time specifying data that specifies a retrieval time, based on the retrieval information and, when that retrieval time is reached, retransmits the response information stored in the memory means 175. That is, in cases where communication cannot be established with the response information receiving equipment 150 concurrently with the communication of the response information over a communication line, the

Thus, even in cases where the response information is transmitted after a delay, response information can be transmitted with certainty by the response information receiving equipment. Moreover, the retrieval transmission processing in the television receiver 160₁ can be controlled by the digital data broadcast from the broadcast unit 140.

10 The detection means 171 detect causes why
communication is not established with the response
information receiving equipment 150. The retrieval
condition alteration means 173, based on the cause so
detected, alter the conditions of retrieval transmission
15 from the next retrieval. Thus flexible retrieval
transmissions can be made according to the cause of
failure.

The display data output means 163, when a read instruction is sent from a user, outputs the response information input to the display means 179. The edit means 177 edit the edit instructions sent from a user and edit the response information stored in the memory means 175.

In this embodiment, by making a display on the
25 display means 179, the configuration facilitates
notification of causes for the non-establishment of

communications, wherefore the display data correspond to notification data. This poses no limitation, however, and this information may be notified by another method such as audio, for example. In that case, the audio data
5 correspond to the notification data.

The configuration may also be such that notification is made of the results of communications with the response information receiving equipment noted earlier. In that way, the user can be informed of response results
10 based on delayed transmissions.

The television receivers 160₂ to 160_n are the same as the television receiver 160₁.

The response information stored in the memory means
175 does not consist only of that which has been input,
15 but may be information generated by response information generation means based on received reception data.

2.3 Transmission Data

In a broadcast system that supports interactive
20 operations, the data structure in the transport stream sent from the transmitter unit is as diagrammed in Fig. 11. In Fig. 11, nothing is indicated about video or audio elementary streams of any service other than the service SV11. The service SV11 is configured of a first
25 video elementary stream ES(V)11, a second video elementary stream ES(V)12, a first audio elementary

stream ES(A)11, and a second audio elementary stream ES(A)12. Thus, at the point where two types of video/audio ES are contained in one service SV11, the data structure differs from that diagrammed in Fig. 3.

5 The configuration is made such that these two types of video/audio ES can be interactively switched between in response to the input of a user on the receiving end, based on navigation data NVT1 and NVT2 which are interactive control data. The configuration also permits
10 additional displays to be interactively altered by input from a user on the receiving end, based on the navigation data.

In Fig. 12 is diagrammed the content of PMT1 for the service SV11. To the control data PMT1 are written PIDs
15 for all the contents (video, audio, navigation data), and a PID for ECM data for obtaining a key to unscramble those contents. In addition, the video, audio, and navigation data all contain multiple contents, wherefore that which is to be output first is written as the entry
20 contents. The PID for these control data PMT1 themselves is "0x0011."

In Fig. 13 is diagrammed the content of the control data PAT. To the control data PAT are written PIDs for PMTs of the services SV11, SV12, SV13, and SV14
25 multiplexed in this transport stream TS1. Thus it can be known that the PID for the service SV11 is "0x0011." The

control data PAT is obtained by receiving the packet attached PID "0x0000" because the PID of the control data PAT is fixedly determined as "0x0000".

The content written in the navigation data NVT1 and NVT2 is diagrammed in Fig. 14 and Fig. 15. With this one set of navigation data NVT1 and NVT2 the same content is repeatedly sent. By means of these navigation data NVT1 and NVT2, as will be described later, service content can be switched between interactively by input from a user.

2.4 Concrete Configuration Example for and Operation of Receiver

In Fig. 16 is diagrammed a hardware configuration diagram for a case where the receiver 160₁ diagrammed in Fig. 10 is implemented with a CPU. In addition to functioning as an ordinary satellite broadcast receiver, this receiver 160₁ has functions also for transmitting response information input by a user to a center. These functions are implemented by a CPU 58 and a program stored in a memory 60. That program may be a program that functions by itself, or one that functions assuming the presence of an operating system (Windows CE made by Microsoft, etc.).

The CPU 58 controls the components according to the program stored in the memory 60.

It is here assumed that the transport stream diagrammed in Fig. 11 is being sent. It is further assumed that the service SV11 contains the video data ES(V)11 and ES(V)12 and the audio data ES(A)11 and ES(A)12, that the video data ES(V)11 and audio data ES(A)12 are television shopping content pertaining to household products, and that the video data ES(V)12 and audio data ES(A)12 are television shopping content pertaining to apparel.

The reception processing program stored in the memory 60 is now described with reference to the flowchart given in Fig. 18.

Assuming that the service SV13 in the transport stream TS1 is being received, the operation involved in sending an instruction to the CPU 58 to switch over to the service SV11 in the transport stream TS1 is described. Instructions are sent to the CPU 58 from a control panel or control remote. The input unit 54 indicated in Fig. 16 is an optical receiver that accepts instructions from the control panel or control remote.

The CPU 58 sets a PID of the control data PAT in a control data separation register (not shown) in a transport decoder (hereinafter referred to as TS decoder) 50. The PID of the control data PAT is fixedly determined as "0x0000." Thus the TS decoder 50 records the content of the separated PAT in the memory 60 (step

S11). In this PAT are written a list of the services that are multiplexed in the transport stream TS1 currently being received (cf. Fig. 13). Accordingly, the CPU 58 knows that the desired service SV11 is multiplexed in the transport stream TS1 currently being received. That is, the CPU 58 advances the processing from step S12 to step S18.

In step S18, based on the fetched the control data PAT, the PID of the control data PMT of the desired service SV11 is fetched. Here, "0x0011" is fetched (cf. Fig. 13). Next, the CPU 58 sets the PID "0x0011" in the control data separation register in the TS decoder 50. Thus the PMT1 of the service SV11 is separated, and the content thereof can be fetched into the memory 60 (step S19).

The PMT1 for the service SV11 is diagrammed in Fig. 12. The CPU 58, based on this PMT1, determines whether or not navigation data NVT is contained in the service SV11 (that is, whether or not this is an interactive service) (step S191). When no NVT are contained, the CPU 58 fetches the PID "0x21" of the ECM data for obtaining the descrambling key for the video and audio data, based on this PMT1. Similarly, it fetches the PIDs "0x22" and "0x24" for the video and audio data ES(V)1 and ES(A)1 (step S20).

The CPU 58 sets the ECM PID "0x21" in the control data separation register in the TS decoder 50 so as to fetch the ECM. It also sends this ECM data to the IC card 56 so as to fetch the restored scrambling key. The scrambling key fetched in this manner is set in the descrambler 48 (step S21). Thus the video data ES(V)1 and audio data ES(A)1 of the service SV11 are rendered in an unscrambled state.

Further, the CPU 58 sets the PIDs "0x22" and "0x24" for the video and audio data ES(V)1 and ES(A)1 in an ES separation register (not shown) in the TS decoder 50 (step S22). Thus the TS decoder 50 outputs the separated video and audio data ES(V)1 and ES(A)1 to an AV decoder 52.

The AV decoder 52, upon receiving these data, expands (restores) the compressed data, performs D/A conversion, and generates a video composite signal. This signal is sent to a TV set 46 and output as video and audio.

On the other hand, when, in step S191, that service contains navigation data, as diagrammed in Fig. 12, the CPU 58 recognizes, from the content of PMT1, the PIDs for the video, audio, and navigation data that are the entry contents, and the PID for that ECM data (step S192). The data recognized here are the PID "0x0096" for the video data ES(V)11, the PID "0x0098" for the audio data ES(A)11,

the PID "0x0092" for the navigation data NVT1, and the PID "0x0082" for these ECM data.

The CPU 58 sets the PID "0x0082" in the control data separation register in the TS decoder 50 so as to fetch the ECM data. The ECM data are also sent to the IC card 56 so as to fetch a scrambling key restored by the IC card 56. In this manner the fetched scrambling key is set in the descrambler 48 (step S193). Thus the service SV11 video data ES(V)11 and ES(V)12, audio data ES(A)11 and ES(A)12, and navigation data NVT1 and NVT2 packets are rendered in an unscrambled state.

The CPU 58 alters the TS decoder 50 filtering conditions, and also interprets and executes the content of the navigation data selected by the TS decoder 50 (step S194). A detailed flowchart for step S194 is described with reference to Fig. 19.

The CPU 58 sets the PIDs "0x0096" and "0x0098" for the video and audio data ES(V)11 and ES(A)11 in the ES separation register (not shown) in the TS decoder 50, and sets the PID "0x0092" for the navigation data NVT1 in the control data separation register (not shown) in the TS decoder 50.

Thus the TS decoder 50 outputs the separated video and audio data ES(V)11 and ES(A)11 to the AV decoder 52. The AV decoder, having received those data, expands (restores) the compressed data, performs D/A conversion,

and generates a video composite signal. This signal is sent to the TV set 46 and output as video and audio. It is assumed here that moving images of household products television shopping, such as diagrammed in Fig. 21, are displayed. Also, the buttons B0 and B1 at the lower right corner of the screen are displayed by the navigation data described later, and are not contained in the video and audio data ES(V)11 and ES(A)11.

The CPU 58, when it receives the navigation data NVT1 from the TS decoder 50, temporarily records those data in the memory 60, and interprets and executes those navigation data NVT1. It is assumed here that navigation data NVT1 such as diagrammed in Fig. 14 have been fetched.

The CPU 58, from the object table in the navigation data NVT1 diagrammed in Fig. 14, sets the object index number "0" as an attention index object (step S202). The CPU 58 displays in the focus mode for the attention index, and a normal mode bit map data for other indexes (step S204). More specifically, because the attention index object is the index "0," control is effected so that data having the bitmap index number "1" are displayed in the focus mode for the index "0" in the object table, while data having the bitmap index number "2" are displayed in the normal mode for the index "1" in the object table. That is, these data are sent respectively to a video synthesizer 52c (cf. Fig. 17) in the AV decoder 52 so

that, for the index "0" in the object table, data having the bitmap index number "1" (highlighted display of "send application to center") are displayed at the position having an X coordinate of "500" and a Y coordinate of "200," and for the index "1" in the object table, the data having the bitmap index number "2" (non-highlighted display of "to apparel shop") are displayed at the position having an X coordinate of "500" and a Y coordinate of "400." Thus the video synthesizer 52c generates video data wherein a highlighted display of "send application to center" and a non-highlighted display of "to apparel shop" are superimposed on the video data ES(V)11. When this is done, a display like that diagrammed in Fig. 21 is obtained wherein the buttons B0 and B1 are superimposed on moving images describing products. As is clear from the screen, a condition is displayed wherein the button B0 "send application to center" has been selected.

The CPU 58 determines whether or not a key input has been made (step S206). When a key input has been made, the CPU 58 determines the type of key input (step S208). In this embodiment, the configuration is made so that a determination is made as to whether a cursor moving key or decision key on the remote 78 diagrammed in Fig. 20 (or on the control panel on the main unit) has been input.

This key type is determined by notification from the input unit 54 (cf. Fig. 16).

When the key input is a cursor moving key, the CPU 58 alters the attention index according to that control (step S210), and performs the display routine in step S204. If the key input is the "key that moves the cursor down," then step S205 is advanced to, the bitmap index in the focus mode for the attention index according to the user control is displayed, and the screen display status is one wherein the button B1 "to apparel shop" has been selected.

In the embodiment described in the foregoing, only those controls with the up and down cursor keys 80 and 82 are indicated. However, if the object index is made in a two-dimensional array, control can also be implemented that supports the left and right keys 86 and 88.

In the condition diagrammed in Fig. 22, when the decision button 84 on the remote 78 is pressed, the CPU 58 advances from step S208 in Fig. 19 to the processing based on step S212. In step S212, the CPU 58 references the navigation data NVT1, and fetches a handler index written in the handler column in the object index currently in the selected condition. Here, the object index "1" has been selected, so the handler index "1" in the handler column is fetched.

In addition, a handler definition table is referenced, and a script corresponding to the handler index "1" is fetched and executed (step S214). Here, "go to contents (index 1)" is fetched. The script "go to contents()" is an instruction to switch to contents having the index number inside the parentheses () indicated in a hyperlink table. Accordingly, a switchover is effected to the contents having the hyperlink index "1" (apparel television shopping) indicated in the hyperlink table.

To the hyper index "1" in the hyperlink table are written the PIDs "0x0097," "0x0099," and "0x0093" for the video, audio, and navigation data, respectively, that are links. The CPU 58 sets the PIDs "0x0097" and "0x0099" in the ES separation register in the TS decoder 50, and sets the PID "0x0093" in the control data separation register therein.

Thus the video data ES(V)12 and audio data ES(A)12 are output to the AV decoder from the TS decoder 50. Thereby, the TV set 46 displays moving images for apparel television shipping as diagrammed in Fig. 23, and outputs audio therefor.

Also, the navigation data NVT2 diagrammed in Fig. 15, is separated by the TS decoder 50, and recorded in the memory 60 in place of the navigation data NVT1. The processing diagrammed in Fig. 19 is executed for these

navigation data NVT2, and the buttons B10 and B12 are displayed as diagrammed in Fig. 23.

In the condition wherein the "send application to center" button B10 has been selected as in Fig. 23, when the user depresses the decision button 84 (cf. Fig. 38), it is possible to make application to purchase products. This process is now described.

When the decision button 84 is depressed, the CPU 58 advances the processing from step S208 to step S212. In step S212, a handler index data is fetched from the index handler column currently in the selected state, following the object display of navigation data NVT2 (cf. Fig. 15). Here, the object index "0" is in the selected state, wherefore the handler index "0" is fetched.

The CPU 58 executes a script corresponding to the handler index "0" in the handler definition table. That is, the script "regist_delayed_connection" is executed. The script "regist_delayed_connection()" is an instruction to register delayed transmission data based on the arguments inside the parentheses ().

Delayed transmission data registration processing is now described. The arguments in the script "regist_delayed_connection()" indicate, in order from the beginning, "order registration number," "transmitting party telephone number," "product code," "service start

time," "initial transmission setting time width,"
 "service end time," and "retrial period."

The CPU 58 generates delayed transmission data based on these arguments. More specifically, while computing
 5 the transmission scheduling time, necessary data are recorded as delayed transmission registration information in the memory 60. For the initial transmission scheduling time, it is only necessary to random-number generate a delay time, within the initial transmission
 10 setting time width, and add the delay time obtained to the service start time. In this case, for example, the initial transmission setting time width is 2 hours, so a random number is computed within the 0 to 2 hour range, and the transmission scheduling time is found.

15 The configuration may also be such that the initial transmission scheduling time is recorded directly in the navigation data NVT1.

In Fig. 24, the delayed transmission registration information generated by this process is tabulated. In
 20 Fig. 24, two sets of delayed transmission registration information generated by navigation data NVT1 and navigation data NVT2 are stored.

When the processing in step S214 is complete, the CPU 58 determines whether or not the executed script was
 25 the script regist_delayed_connection() (step S216). If the executed script was not the script

regist_delayed_connection(), then, in that case, it is a contents-switching script, wherefore the processing in step S200 and following is repeated. If, on the other hand, the executed script was the script
 5 regist_delayed_connection(), then, in that case, the processing diagrammed in Fig. 19 ends.

Thus the reception processing ends.

2.5 Delayed Transmission Processing

10 The delayed transmission processing adopted in this embodiment is now described with reference to Fig. 25 and Fig. 26. The description here assumes that the delayed transmission registration information diagrammed in Fig. 24 is stored in the memory 60.

15 The CPU 58 determines whether or not there is registration information in the delayed transmission registration information table in the memory 60 (step S301 in Fig. 25). In this case, there is registration information in the delayed transmission registration
 20 information table, so the delayed transmission registration information having the earliest transmission scheduling time is read out (step S303). In this case, the delayed transmission registration information having the order registration number "007" is earlier than that
 25 having the order registration number "001," so the delayed transmission information having the order

registration number 007 is read out. More specifically,
the order registration number "007," the transmitting
party telephone number "06-6900-xxxx," the product code
"B-133," the transmission scheduling time
5 "1999.1.10.13:30:00," the service end time
"1999.10.16:00:00," and the retrial period "10 minutes"
are read out from the memory 60.

The CPU 58 determines whether or not the current
time coincides with the transmission scheduling time
10 "1999.1.10.13:30:00" (step S305). If the current time
does not coincide with the transmission scheduling time,
a determination is made as to whether or not there has
been any change in the registration information in the
delayed transmission registration information (step S307).
15 If there has been no change in the registration
information, then the decision routine in step S305 is
repeated. If, however, there has been a change in the
registration information, step S301 is returned to, and a
decision is made as to whether or not the registration
20 information is present.

When in step S305 the current time does coincide
with the transmission scheduling time, the registration
information in view is transmitted according to the
communications protocol (step S309). If this is the case,
25 then the transmission is made as follows. The CPU 58
fetches the delayed transmission information having the

transmitting party telephone number "06-6900-xxxx," controls the line communication unit 76 indicated in Fig. 16, and calls the number "06-6900-XXXX." This is the telephone number of the television shopping reception center. When the call goes through, the CPU 58 transmits the argument data "product code:B-133" and an ID for specifying the product purchaser. Such a product purchaser ID may be fetched from the IC card 56 or from the memory 60, for example. Thus the order for the product designated by the user is concluded.

The CPU 58 determines whether or not the communication was successful (step S311), and, if successful, records the transmission results ("successful" in this case) in the memory 60 (step S313). The CPU 58 deletes that delayed transmission registration information (step S315), and then repeats the procedures from step S301 on.

If, in step S311, the communication was not successful, on the other hand, the CPU 58 records the results of that transmission ("failed" in this case) in the memory 60 (step S321 in Fig. 26). An example of such a case would be where the center telephone was busy.

The CPU 58 determines whether or not retrials should be suspended (step S323). This determination will be described subsequently.

When the CPU 58 has determined that retrials should not be suspended, the transmission scheduling time for the failed order registration number must be rewritten in order to permit automatic retrial (step S325). More specifically, the retrial period is added to the current order scheduling time, and the result is rewritten as a newly computed transmission scheduling time. If this is the case, the new transmission scheduling time becomes "1999.1.10.13:40:00."

The CPU 58 determines whether or not the new transmission scheduling time "1999.1.10.13:40:00" exceeds the service end time (step S327). In this case, the new transmission scheduling time does not exceed the service end time "1999.1.10.16:00:00" indicated in Fig. 24, so the processing is repeated from step S301 on in Fig. 25.

In step S327 in Fig. 26, if the new transmission scheduling time does exceed the service end time, the CPU 58 records the transmission results ("out of time" in this case) (step S329). The CPU 58 also deletes that registration information (step S331).

Thus the processing flowcharted in Fig. 25 and Fig. 26 is repeated.

The transmission results recorded may also, when the order has gone through, for example, be output so that notification thereof can be made. For example, in a case where, in terms of transmission result, the order having

the order registration number "007" was not successful prior to the service end time but the order having the order registration number "001" was successful, communication results such as are diagrammed in Fig. 27 are displayed on the TV set 46. In this example, the response information for order registration number 001 is "13:52 busy," "13:57 busy," . . . "14:12 successful," while the response information for order registration number 007 indicates "13:30 busy," "13:40 busy," . . .

10 "16:00 time out."

By displaying such a log as this, the user can learn whether or not an application to purchase a product was processed properly. The times for communications made may be fetched from control data TDT contained in the transport stream, or from an internal calendar or clock, etc., in the CPU itself. Alternatively, the configuration may be made so that the communication results make notification when an order fails as well as when it succeeds. This may be done, for example, by lighting a LED mounted on the main unit or making a display on the monitor in each case. Or these results may be made in summary form. A transmission history of response information may be stored in memory and displayed as a list, for example. Alternatively, the transmission history may be displayed so as to show the

15

20

25

response information separately for each order registration number.

2.6 Cause Detection Processing for Delayed

Transmissions

5 The processing in step S323 in Fig. 26 is described next. In this embodiment, if communication processing with the center has not been completed, until the service end time, based on the retrial period sent from the broadcasting station, retrial processing is altered
10 according to the reason why communication cannot be effected with the center, instead of finding the transmission scheduling time and repeating the retrial processing.

 In this embodiment, the conditions for suspending
15 retrial processing are stored in memory, and retrial processing which matches the conditions concerning which the failure reason was stored in memory in step S321 is suspended. An example of this is the case where the telephone call with the other party was established but
20 connection could not be made with the other party's modem. In this case, it is possible that the other party's telephone number in the navigation data indicated in Fig. 14 is in error. In such cases, it is unlikely that communication can be established by repeating the retrial
25 processing.

Another case of suspending retrial processing is one where the telephone call to the center does not go through within a prescribed number of retrials, for example. In this case, it is possible that the connector from the receiver to the telephone has been unplugged, whereupon the call will not go through to the center no matter how many retrials are made. In this case, the fact of being unable to get a call through to the other party constitutes an anomalous situation, wherefore retrial processing is suspended. In this case also, moreover, provision may be made for displaying a message to please confirm that the telephone cord has not become disconnected. Provision may also be made so that, after that message is displayed, another retrial will be made after a confirmation button has been depressed.

In this embodiment, delayed transmissions are made, wherefore it is very difficult for a user to know when the transmitter sent the response information. There are also cases where the telephone line described in the foregoing is shared between an ordinary telephone and the receiver. In that case, it is possible that the user is using that telephone line. In that case, when the telephone use by the user has terminated, that may be detected, and a time that is a prescribed number of seconds thereafter (10 seconds later, for example) may be determined as the transmission scheduling time.

2.7 Computation of Initial Scheduled

Transmission Time

The following procedure may also be used for
5 computing the initial transmission scheduling time
described in the foregoing. If a probability density
function with time plotted on the horizontal axis and
probability density on the vertical axis, as diagrammed
in Fig. 28A, is sent from the broadcasting station, then,
10 on the receiving end, based on that function, a random
number may be generated to determine the initial
transmission scheduling time.

The probability density function diagrammed in Fig.
28A is a function wherewith the probability density is 2
15 from start to 30 minutes, and the probability density is
1 from 30 minutes to 1 hour. This function can be
defined, for example, as {(00:00:00 - 00:29:59, 2),
(00:30:00 - 00:59:59, 1)}. Thus, by employing
probability variation data wherein the probability
20 density changes as time elapses, the delayed transmission
on the receiving end can be definitely controlled by the
transmission end. This is so for the following reason.

It is possible to predict the frequency of telephone
responses for a given product, to some degree, by an
25 experiential rule of thumb. Ordinarily, the quantity of
telephone lines made available at the center is

determined in view of such a prediction. For example, 100 lines might be made available from start to 30 minutes, and the number then reduced to 50 lines after 30 minutes have elapsed. Accordingly, the communication lines made available for the response information receiving equipment cannot be effectively used merely by simply delaying and dispersing the responses from the receiving end. However, by sending probability variation data that matches the number of communication lines made available from the sending end, as described above, and determining the initial transmission scheduling time by a random number based thereon, responses will be made with roughly that probability. Thus the communication lines made available in the response information receiving equipment can be used effectively.

A procedure for determining the transmission scheduling time when such a probability density function is used is now described. On the receiving end, a random number is generated as the maximum value for a random number for the area (hatched portion) defined by the function described earlier, and a time corresponding to that value is computed. With the function diagrammed in Fig. 28A, for example, the overall area is

$$30 * 60 * 2 + 30 * 60 * 1 = 3600 + 1800 = 5400.$$

The * 60 factor is included because the time is expressed in seconds.

000140" 15854560

A random number is thus generated having this 5400 as the maximum value of the random number. Then the delay time is computed so that the random number obtained coincides with the area. In this case, the probability density is changed at the 3600 boundary, wherefore, in cases of 3600 or less, such as, for example, when 388 is the random number generated, the transmission will be made after $388/2 = 194$ seconds, that is, after 3 minutes 14 seconds, as diagrammed in Fig. 28B. When a random number of 5000 is obtained, on the other hand, the transmission will be made after $(5000 - 3600) + 1800 = 3200$ seconds, that is, after 53 minutes 20 seconds, as diagrammed in Fig. 28C.

It is also permissible to specify the probability variation data with a probability distribution function like that diagrammed in Fig. 29 instead of with a probability density function like that diagrammed in Fig. 28. Fig. 29a represents Fig. 28a with a probability distribution, with generated random number values plotted on the vertical axis and time on the horizontal axis. This function can be defined, for example, as $\{(00:29:59, 3600), (00:59:59, 5400)\}$. The receiver generates a random number as the maximum value of a random number for the maximum value on the vertical axis in such a graph, finds the corresponding time on the horizontal axis, and makes that the delay time. Assuming, for example, that

the value of the random number generated is 388, if the value of the random number generated is 3600 or less, then the definition is made $t = 1/2y$. The transmission will therefore be after $388 * 1/2 = 194$ seconds, that is, after 3 minutes 14 minutes, as diagrammed in Fig. 29B. If the random number 5000 is obtained, on the other hand, the definition will be made with $t = y - 1800$, and the transmission will be made after $5000 - 1800 = 3200$ seconds, as diagrammed in Fig. 28C, that is, after 53 minutes 20 seconds.

It is possible, furthermore, to determine not only the initial transmission scheduling time, but also the time to initiate a retrial, based on these probability variation data, without using the retrial period.

Moreover, instead of the procedure described above for dispersing the initial transmission scheduling time, delay dispersion processing may be done based on a time created by a user, or the ID of that receiver, etc., for example, as conventionally.

3. Other Embodiments

In this embodiment, the data format for the arguments in the navigation data has been described for the case where those data are text data, but the data format is not limited thereto, and may be a binary format.

Neither is there any limitation on the type of arguments or on the order in which they are deployed in a script.

In the embodiment described in the foregoing, furthermore, provision is made to determine whether or not retrials should be suspended, but provision may also be made to alter the retrial conditions. For example, instead of making the retrial period a constant time period, such as every 5 minutes, for example, provision may be made so that the period can be altered according to the situation. Provision may be made, for example, to broadcast data to make the retrial period shorter as the service end time is approached. Alternatively, data may be transmitted to make the retrial period shorter when the number of retrials exceeds a certain number.

In the embodiment described in the foregoing, furthermore, provision is made so that the decision on whether or not to alter the retrial conditions is made autonomously, on the receiver end. However, provision may also be made to alter the retrial conditions based on a rewrite instruction from the center. In that case, the receiver may be made to determine whether or not a rewrite instruction has been received, instead of making the decision in step S323.

It is further permissible to configure such that the broadcast station is made to broadcast the condition alteration instruction noted above, so that the receivers

receiving that instruction will alter the corresponding registration information, in whole or in part.

In this embodiment, description is given for the case where the conditions for altering the retrieval processing are stored beforehand in the data receiver. However, provision may be made so that this is rewritten when a rewrite instruction is transmitted from the receiving end. Moreover, provision may be made so that a plurality of such conditions are established, so that any one can be designated for each incidence of delayed transmission registration information. Provision may also be made so that different retrieval processing alteration conditions can be established for each script.

The registration information capable of editing from the transmitting end may be made any data in the delayed transmission registration information. Those data may be, for example, a retrieval period that is retrieval control information, or a product code that is response information, or a transmission scheduling time that is delayed transmission control information. For the various data subject to editing, moreover, the order registration number may be designated and an instruction transmitted to rewrite these directly, or, alternatively, a recomputation may be enforced. For the procedure for enforcing a recomputation, arguments in the script can be resent, and/or provision may be made to reference values

in the navigation data for some of the arguments. Alternatively, only differential data may be sent. For example, for data having some registration number, a value to be added to the current retrieval period may be transmitted as differential data, and recomputation enforced on the receiving end based on those differential data.

In cases where a plurality of data sets are merged, moreover, it is permissible to send only a merge instruction. In that case, the receiver that receives the merge instruction may reference two product codes, and synthesize those into one set of data having the two product codes. Also, provision may be made to delete the other registration data. In a case, for example, where the registration number 002 is the product code C200, the registration number 003 is data for purchasing the product code C300, and both are order information to be telephoned to the same center, provision may be made so that, when the merge instruction is received, the receiver reads the product code C300 from the registration number 003, rewrites the registration information for the registration number 002 to the product codes C200 and C300, and deletes the registration information for the registration number 003.

In this embodiment, description is given for cases where application is made to television receivers.

However, application is possible in any situation whatever so long as there is a data receiver which receives broadcast data, and transmits response information that is either input thereto or automatically
5 generated.

In this embodiment, furthermore, description is given for cases where public analog lines are used as the communication lines between the center and the data receivers. However, either ISDN lines or dedicated lines
10 may also be used. In the case of dedicated lines, the delayed transmission registration information stored in memory may be the other party's ID instead of that party's telephone number.

In the embodiment described in the foregoing,
15 moreover, provision is made for notifying a user of the results of a response to the center by displaying log data stored inside the receiver. However, it is also permissible to configure such that, when the center receives response information, a different communication
20 medium such as a fax machine is used to notify the user that a delayed transmission was completed. The communication medium used here may be an automatic voice notification made by telephone, an electronic mail (e-mail) message, or a message function such as EMM
25 (entitlement management message) in a satellite broadcast. By notifying the user of such data as these stored in the

center by broadcast or by another line, a user can be notified of the results of responses with the center. Thus a user can be definitely notified that response information was received, either by another communication
5 medium using the same line as the communication line between the center and the receiver, or by a communication line different from the communication line between the center and the receiver.

The registration information represented in Fig. 24
10 may also be displayed in a list on the screen. Provision may further be made so that, when the user selects items from among those displayed in the list, more detailed information (product image, price, etc.) can be displayed. Provision may also be made so that the user can edit the
15 items displayed in the list. Alternatively, provision may be made to display sequentially instead of in a list.

In the embodiment described in the foregoing, moreover, description is given for the case where two types of video/audio ES are contained in one service SV11.
20 However, the configuration may also be made so that one type of video/audio ES is transmitted in one service, and products described by video data change over time. In that case, provision may be made for transmitting navigation data having differing content corresponding
25 thereto (having different product codes with an index of "2" in a character string table).

In the embodiment described in the foregoing, furthermore, a case is represented that is based on two video/audio data and two sets of navigation data. However three or more video/audio data and three or more
5 sets of navigation data may be used. Alternatively, one set of navigation data may be used for a plurality of video/audio data, or a plurality of sets of navigation data may be used for one video/audio data.

In the embodiment described in the foregoing,
10 moreover, provision is made to transmit, and receive, moving images as the video data. However, it is permissible to have still images transmitted, and received, as the video data. More specifically, as diagrammed in Fig. 30, by repeatedly sending one set of
15 still images A, B, C, and D, as the video data ES, and writing the link relationships between these multiple still images A, B, C, and D into a hyperlink table and an object table in the navigation data, an interactive service can be realized as in the case of moving images
20 described earlier.

Also, for products which could be purchase-registered or products for which purchase-registration failed, provision may be made so that product specification information such as product names and still
25 images are stored in memory, and these are displayed after communications are completed.

000140 T5854560

In the present invention, moreover, what are called products are not limited to tangible objects, but include intangible services. Also, television shopping is described as an example, but the present invention can similarly be applied to viewer rating surveys, questionnaire information collection, and quiz shows, etc.. Applications are also possible in cases where a computer-understandable request is broadcast, and collection data in a receiver are sent to a center, as in systems for charging fees for software (including contents as well as programs). In such cases, real response data corresponding to a product code, and a real response data ID that is an identifier for those real response data corresponding to an order registration number, may be sent to a center.

In this embodiment, furthermore, the case is described where a user inputs response information, but provision may be made so that response information is generated on the basis of data input by a user. In an example cited earlier, for example, the transmission scheduling time is not data input by the user, but is generated in response to data input by the user. Alternatively, this may be automatically produced by a data receiver, without data being input by the user. In the case of viewer rating surveys, for example, the

response information can be automatically generated by the receiver.

In this embodiment, moreover, the service start time is later than the actual broadcast time. Accordingly, the user of a data receiver can enjoy the advantages provided by a particular service even in cases where the broadcast data are stored on hard disk or other recording medium, and then viewed in a viewable time period. In cases where a response was made after the broadcast started but before the service start time, in particular, delayed transmission is made from the receiver in response to the probability variation data described earlier.

In this embodiment, from the sending end, the telephone number of the transmitting party is used as a response information receiving equipment identifier, the product code is used as a response information number, and the service start time, initial transmission setting time width, service end time, and retrial period are used as delayed transmission control data. However, it is only necessary for the delayed transmission control data that data be included for controlling the delayed transmission, and provision may be made, for example, for storing the maximum number of retrials in memory instead of the service end time.

000740-15254550

In this embodiment, furthermore, the description assumes the case where the broadcasting end and receiving end constitute one-to-many broadcasting, while the receiving end and response information receiving end constitute one-to-one communications. However, application is similarly possible in computer networks such as that diagrammed in Fig. 31. In Fig. 31, a server 200 is a WWW server, connected to the internet, which stores a plurality of contents, and, upon receiving a request, sends the corresponding contents to the computer of the requesting entity. In this case, when requests are made simultaneously from the computers 210, 220, 230, 240, and 250, if the contents to be distributed involve an enormous data volume, and the capacity of the line 201 is exceeded, a situation will arise wherein, during download, requests cannot be accepted from other computers. This might be a situation wherein download requests are concentrated in a particular period of time, as when a version upgrade has been released, for example. In such cases as this, the request concentration is a temporary phenomenon, and more often than not the concentration problem will no longer arise once that period has passed. In such cases as this, effective utilization is possible without increasing the capacity of the line 201 by taking the measures described below.

When requests are tendered simultaneously from the computers 210, 220, 230, 240, and 250, a download request delay control program is distributed to all the computers. That delay control program is a program which disperses the sending of the download start request already described to the server, and includes delay control information for delay processing. This delay control processing need only be capable of delayed transmissions, and is not limited to the delay processing described earlier.

Each computer computes transmission scheduling times based on the delay control information described earlier and stores them in memory. When a transmission scheduling time is reached, a download request is sent to the server 200. Thus, even if requests from the computers are concentrated, delay-dispersion can be effected. Accordingly, it is possible to disperse the requests coming from the computers according to the capacity of the line 201.

In this example, provision is made for making the dispersion in a time sequence. However, if a mirror site is available, the configuration may be such that the server 200 checks to see how busy the server at the mirror site is, and, depending on how busy it is, sets the other-party ID of the delay control program described above for some computers so that they download from the

mirror site, so that download requests are dispersed between [itself and] the mirror site.

It is also permissible to divide the download server IDs according to the geographical location of the
5 computers making the requests, and not only on how busy a mirror-site server is.

There are also cases where the computers are not always connected to the internet, but connect to an internet service provider computer over telephone lines.
10 Provision may be made so that, in cases such as that, when the delayed transmission time is reached, calls are automatically made to connect to the internet, and download requests are then made. There are also cases where power to a computer is turned off. Provision may
15 be made so that, in such cases as that, a power supply management program is left running, and, when the delayed transmission time is reached, the power is turned on and a download request is transmitted.

In order to tell whether a download request based on
20 a delayed transmission is the first download request or not, provision may be made for sending data for making that distinction from the transmission-delaying program described earlier. In this embodiment, furthermore, the navigation data are transmitted together with the video
25 data and audio data, but those data may be only the navigation data. In the case described, scripts are

imbedded in the navigation data, so that execution processing is done on the receiving end based on those scripts. However, provision may be made for transferring HTML data. In that case, a browser program may be made
5 available for interpreting and displaying the HTML data on the receiving end. It is permissible, moreover, to use such structural programming language data as SGML data, XML data, or MHEG data, etc., as well as HTML data.

In other words, the present invention can be applied
10 in all cases where a center transmits transmission request data to the broadcasting entity, data receivers receive those transmission request data, and collection request data manually input or collection request data automatically input based on the transmission request
15 data are sent to the center.

In the embodiment described in the foregoing, the response information receiving equipment can receive response information from television receivers according to the allowable volume on the communication lines made
20 available to the response information receiving equipment. There will be cases, however, where the number of responses is greater than or less than the predicted allowable volume. Provision may be made so that, in such cases, rewrite information is sent from the response
25 information receiving equipment 150 to the broadcast unit 140 for rewriting the delayed transmission registration

information stored in the receivers, and broadcast simultaneously. In a case where, for example, there are more orders than the predicted volume for the order registration number "007," and the predicted volume has
5 been sold out, rewrite information would be broadcast from the broadcasting entity to the receivers to cause the service end time for that order registration number "007" to be rewritten to the current time. The receivers receiving that information reference their own delayed
10 transmission registration information table and, if order information for that order registration number "007" is present, rewrite the service end time to the present time. Thus responses from the receivers can be suspended.

In the case described above, provision is made for
15 suspending the responses, but provision may also be made to extend the service end time or alter the retrial period. Provision may also be made for altering the probability variation data described earlier. That is, the data for controlling the delayed transmission can be
20 controlled from the transmitting end. For example, provision may be made so that a script is broadcast which consolidates two sets of registration information going to a center having the same telephone number into one set of registration information, a delayed transmission
25 registration information table is referenced on the receiving end, and that script is executed. The process

for effecting such consolidation can be made so that communications effectiveness is optimized on the receiver end. With some broadcasts, however, there are cases where, even with the same telephone number, such
5 consolidation is not desirable. In such cases as that, it will be preferable that the process on the receiving end be controlled on the transmitting end.

In this embodiment, provision is made for storing a display program in memory. It is permissible, however,
10 to store such a program in an IC card, CD-ROM, or other recording medium, and then transfer the program via the IC card drive or CD-ROM drive to nonvolatile memory for storage. Such a program may also be transferred by communications and stored in nonvolatile memory.

15 In this embodiment, provision is made for fetching an ID for specifying a product purchaser from the IC card 56 or the memory 60, and transmitting it. However, it is also permissible to send a script as navigation data that will cause the name and address, etc., to be input on the
20 screen.

Provision may also be made to store the delayed transmission registration information described earlier in rewritable nonvolatile memory. By so doing, that delayed transmission registration information can be
25 saved even when the power supply fails as in a power outage.

In the embodiments described in the foregoing, the functions realized using a CPU may be implemented in whole or in part in hardware. In any of those embodiments, moreover, the functions implemented by hardware may be implemented in whole or in part using a CPU.

1) The data transceiving system relating to the present invention is a data transceiving system wherein data are sent from a broadcasting station to a plurality of television receivers by broadcasting, and response information is sent from the television receivers to response information receiving equipment by communication lines, wherein the broadcast station makes transmissions inclusive of retrieval information to enable the television receivers to make retrieval transmissions when the television receivers are unable to establish communications with the response information receiving equipment. Accordingly, the response information receiving equipment can more definitely receive the response information, even when the response information is transmitted after a delay. Furthermore, the retrieval transmission processing in the television receivers can be controlled by data broadcast from the broadcast station.

2) In the data transceiving system relating to the present invention, the television receivers, upon

receiving data containing retrial information to enable
retrial transmissions with the response information
receiving equipment when communications are not
established with the response information receiving
5 equipment, retransmit the response information on the
basis of that retrial information. Accordingly, the
response information receiving equipment can more
definitely receive the response information even when the
response information is transmitted after a delay.
10 Furthermore, the retrial transmission processing in the
television receivers can be controlled by data broadcast
from the broadcast station.

3) In the data transceiving system relating to the
present invention, the broadcast unit sends retrial
15 information according to the allowable volume of the
communication lines, included in the data, and the
television receivers retrial-transmit the response
information on the basis of the retrial information
received when communications are not established with the
20 response information receiving equipment. Accordingly,
the response information receiving equipment can more
definitely receive the response information even when the
response information is transmitted after a delay.
Furthermore, the broadcast unit can control the retrial
25 transmission processing according to the allowable volume
on the communication lines.

4) In the television receiver or data transceiving method relating to the present invention, in cases where communications could not be established with the response information receiving equipment, the response information is retrial-transmitted to the response information receiving equipment, on the basis of the retrial information received from the broadcast unit. Accordingly, the response information receiving equipment can more definitely receive the response information even when the response information is transmitted after a delay. Furthermore, the retrial transmission processing can be controlled with data broadcast from the broadcast station.

5) The data receiver relating to the present invention comprises means for receiving data sent from a broadcast unit, means for outputting display data based on those received data to display means, and communication means, being means that transmit response information over communication lines, for retrial-transmitting the response information, on the basis of retrial information contained in those data received from the broadcast unit, when communications could not be established with the response information receiving equipment. Accordingly, the response information receiving equipment can more definitely receive the response information even when the response information

is transmitted after a delay. Furthermore, the retrieval transmission processing in the data receiver can be controlled with data broadcast from the broadcast station.

6) The television receiver relating to the present invention comprises means for receiving data sent from a broadcast unit, means for displaying display data based on those received data, and communication means, being means that transmit response information over communication lines, for retrieval-transmitting the response information, on the basis of retrieval information sent from the broadcast unit, when communications could not be established with the response information receiving equipment. Accordingly, the response information receiving equipment can more definitely receive the response information even when the response information is transmitted after a delay. Furthermore, the retrieval transmission processing in the television receiver can be controlled with data broadcast from the broadcast station.

7) The television receiver relating to the present invention specifies an initial transmission scheduling time with the response information receiving equipment, by random computation based on received delay information. Accordingly, the initial transmission scheduling time can be dispersed by the receiving end even when one delay information is broadcast from the broadcast station.

8) The television receiver relating to the present invention determines whether or not to make retrial transmissions based on a transmission end time sent from the broadcast unit. Accordingly, retrial transmissions
5 can be suspended on the basis of the transmission end time.

9) The television receiver relating to the present invention comprises detection means for detecting causes of non-establishment of communications with the response
10 information receiving equipment. Thus, by detecting the causes for communications failures, suitable action can be taken.

10) In the television receiver relating to the present invention, retrial condition alteration means
15 alter the conditions for retrial transmissions from the next time on, based on the cause detected. Accordingly, retrial transmissions can be made with different condition depending on the communication failure cause detected.

20 11) In the television receiver relating to the present invention, the retrial condition alteration means alter the retrial transmission setting time width. Accordingly, retrial transmissions can be made with different setting time widths depending on the
25 communication failure cause detected.

12) In the television receiver relating to the present invention, the retrial condition alteration means suspend retrial transmissions. Accordingly, retrial transmissions can be suspended depending on the communication failure cause detected.

13) In the television receiver relating to the present invention, notification data are generated for notifying notification means of the detected cause. Based on these notification data, users can be notified of communication failure causes.

14) In the television receiver relating to the present invention, time remaining for transmission is computed from a transmission end time sent from the broadcast unit, and the retrial transmission conditions are altered according to the time remaining for transmission. Accordingly, different retrial transmissions are possible depending on the time remaining for transmission.

15) In the television receiver relating to the present invention, notification data are generated for making notification of results of communications with the response information receiving equipment. Based on these notification data, users can be notified of the results of communications.

16) In the television receiver relating to the present invention, communication results are received

from the response information receiving equipment and notification data for making notification thereof are generated. Accordingly, notification data can be generated which are based on the response information
5 stored in the response information receiving equipment.

17) In the television receiver relating to the present invention, a history of communications with the response information receiving equipment is stored in memory, and notification data are generated. Accordingly,
10 notification data can be generated which are based on the communications history with the response information receiving equipment.

18) In the television receiver relating to the present invention, the response information transmitted
15 after the delay is stored in memory, and, when a notification instruction is sent from a user, notification is made of the response information. Thus a user can confirm the response information sent after the delay.

19) In the television receiver relating to the present invention, editing means edit the response information when an edit instruction is sent from a user. Thus a user can confirm response information subject to delayed transmission and edit that information to achieve
25 suitable response information.

20) In the data receiver relating to the present invention, the communication means retrieval-transmit the response information, based on retrieval information contained in the data received, when communications could not be established with response information receiving equipment. Accordingly, the response information receiving equipment can more definitely receive the response information even when the response information is transmitted after a delay. Furthermore, the retrieval transmission processing in the data receiver can be controlled with broadcast data.

21) In the data receiver relating to the present invention, when communications with the response information receiving equipment could not be established, retrieval time specifying data are computed for specifying the retrieval time, based on the retrieval information, and, when the retrieval time is reached, the response information stored in memory is retransmitted. Accordingly, the response information receiving equipment can more definitely receive the response information even when the response information is transmitted after a delay. Furthermore, the retrieval transmission processing in the data receiver can be controlled with broadcast data.

22) The data receiver relating to the present invention specifies an initial transmission scheduling

time with the response information receiving equipment,
by random computation based on received delay information.
Accordingly, the initial transmission scheduling time can
be dispersed on the receiving end even when one set of
5 delay information is broadcast from the broadcast end.

23) The data receiver relating to the present
invention determines whether or not to make retrieval
transmissions based on a transmission end time sent from
the broadcast unit. Accordingly, retrieval transmissions
10 can be suspended on the basis of the transmission end
time.

24) The data receiver relating to the present
invention comprises detection means for detecting causes
of non-establishment of communications with the response
15 information receiving equipment. Thus, by detecting the
causes for communications failures, suitable action can
be taken.

25) The data receiver relating to the present
invention is a data transceiving system wherein data are
20 sent from a broadcasting station to a plurality of data
receivers by broadcasting, and response information is
sent after a delay from the plurality of data receivers
to response information receiving equipment by
communication lines, and wherein the broadcast station
25 sends retrieval information contained in those data, the
data receiver resends the response information based on

the retrieval information when communications could not be established with the response information receiving equipment, and the response information receiving equipment, upon receiving the response information from the data receiver, notifies the user of the data receiver that response information was received by a communication line other than those communication lines. Accordingly, conformation can be made as to whether or not response information could be sent to the response information receiving equipment in cases where the response information was transmitted after a delay.

26) The data receiver relating to the present invention comprises a tuner for selecting a transport stream from data sent from a broadcast unit, a transport decoder for selecting display data of a desired service from the selected transport stream, an AV decoder for outputting the display data of the selected service to a monitor, a control input unit wherewith a user inputs response information, a line communication unit for sending the response information over a communication line, a CPU, and a memory in which a control program for the CPU is stored, wherein the control program retrieval-transmits the response information via the line communication unit, based on the retrieval information contained in the data, when communications could not be established with the response information receiving

equipment. Accordingly, in cases where the response information was transmitted after a delay, confirmation can be made as to whether or not the response information could be sent to the response information receiving
5 equipment.

27) In the data transceiving system relating to the present invention, the server, upon receiving the download request, sends a download request transmission-
10 delaying program to the computer making that download request, and the computer sends a download request, after a delay, to the server, based on the download request transmission-delaying program. Accordingly, it is possible to execute download requests and download processing at different times. Thus download requests
15 can be prevented from concentrating.

28) The server in the data transceiving system relating to the present invention is a server connected to a plurality of computers which, upon receiving a download request from any computer, does not cause data
20 specified by that download request to be transmitted to the computer making that download request, but rather sends thereto a download request transmission-delaying program which sends download requests to the server after a delay. Accordingly, the timing of the process of
25 actually downloading to the computer can be shifted.

29) The data transceiving system relating to the present invention comprises 1) a broadcast unit for broadcasting data, 2) a plurality of television receivers for receiving the data, effecting displays based on the received data, and transmitting response information over communication lines, and 3) response information receiving equipment connected to the television receivers via the communication lines for receiving response information from the television receivers, wherein the broadcast unit sends probability variation data, included in the aforesaid data, wherewith the probability of generating a transmission time varies over time, and the television receivers determine transmission scheduling times for transmitting to the response information receiving equipment on the basis of the received probability variation data. Accordingly, when response information is caused to be transmitted after a delay in the television receivers, retrial transmission processing can be performed according to the allowable volume on the communication lines.

30) The data transceiving system relating to the present invention is a data transceiving system for transmitting data by broadcast from a broadcast station to a plurality of television receivers and transmitting response information from the television receivers to response information receiving equipment by communication

lines, wherein the television receivers, upon receiving probability variation data wherein the probability wherewith transmission times are generated varies over time from the broadcast unit, determine transmission scheduling times for transmitting to the response information receiving equipment on the basis of the received probability variation data. Accordingly, when response information is transmitted after a delay, retrieval transmission processing is performed according to the allowable volume on the communication lines.

31) In the data receiver relating to the present invention, when probability variation data wherein the probability wherewith transmission times are generated varies over time are received from the broadcast unit, the transmission scheduling time for transmitting to the response information receiving equipment is determined on the basis of the received probability variation data. Accordingly, retrieval dispersion transmission processing is possible according to the allowable volume on the communication lines.

32) In the data receiver relating to the present invention, when a transmission start enabled time is received from the broadcast unit, the time until the transmission scheduling time is random-number generated using the received probability variation data, and the transmission scheduling time is determined. Accordingly,

retrial dispersion transmission processing is possible according to the allowable volume on the communication lines.

33) In the data transceiving method relating to the present invention, when data inclusive of retrial information according to the allowable volume on the communication lines are received, when communication could not be established using the communication lines, the response information are retrial-transmitted on the basis of the received retrial information. Accordingly, response information can be more definitely received, even when the response information is transmitted after a delay. Furthermore, retrial transmissions are made according to the allowable volume on the communication lines.

34) The data transceiving method relating to the present invention is a data transceiving method which transmits response information over communication lines when broadcast data are received, wherein the data include probability variation data wherewith the probability of generating a transmission time varies over time, and the transmission scheduling time for transmitting over the communication lines is determined on the basis of the received probability variation data. Accordingly, the response information can be transmitted

after a delay according to the allowable volume on the communication lines.

35) In the recording medium for storing a program, relating to the present invention, the program performs the following processing, namely, when communications could not be established with the response information receiving equipment, the response information are retrieval-transmitted to the response information receiving equipment on the basis of retrieval information received from the broadcast unit. Accordingly, response information can be more definitely received, even when the response information is transmitted after a delay. Furthermore, retrieval transmissions are made according to the allowable volume on the communication lines.

36) In the recording medium for storing a program, relating to the present invention, the program performs the following processing, namely, 1) when probability variation data wherewith the probability of generating a transmission time varies over time are received, a transmission scheduling time for transmitting to the response information receiving equipment is determined on the bases of the received probability variation data. Accordingly, retrieval dispersion processing is possible according to the allowable volume on the communication lines.

000110 15354550

In this invention, the term "recording medium for storing a program" refers to a recording medium such as a ROM, RAM, flexible disk, CD-ROM, memory card, or hard disk, etc., on which a program is recorded. This concept
5 also includes such communication media as telephone lines and transport routes. The concept also includes such recording media as CD-ROMs, etc., on which are recorded programs which are executed after first being installed on a hard disk or the like, and is not limited to
10 recording media such as hard disks wherewith the recorded program is executed directly. Moreover, what is here called a program is inclusive of program source code, compressed programs, and encrypted programs, and is not limited to immediately executable programs. Furthermore,
15 the navigation data in the embodiments are also included in this program concept.

The term "television receiver" refers of course to a set top box that is connected directly to a monitor, but is also inclusive of television receivers that have a
20 built-in monitor.

The language "editing of input response information" refers of course to cases where actual data in input response information are altered, in whole or in part, but also includes the deletion of such response
25 information.

The term "response information" refers to the data themselves that have been input by the user of a data receiver, to that which has been generated on the basis of data input by the user of a data receiver, to that
5 which has been generated on the basis of received data, and to that which has been automatically collected.

While the embodiments of the present invention, as disclosed herein, constitute preferred forms, it is to be understood that each term was used as illustrative and
10 not restrictive, and can be changed within the scope of the claims without departing from the scope and spirit of the invention.

1. A data transceiving system wherein:
data are sent from a broadcasting station to a
plurality of television receivers by broadcasting;

said broadcast station makes transmissions inclusive of retrieval information to enable said television receivers to make retrieval transmissions when said television receivers are unable to establish communications with said response information receiving equipment.

response information is sent from said television receivers to response information receiving equipment by communication lines; and

25 with said response information receiving equipment,

retransmit said response information on basis of that
retrial information.

3. A data transceiving system comprising:

5 a broadcast unit for broadcasting data;

a plurality of television receivers for
receiving said data and transmitting response information
over communication lines; and

10 response information receiving equipment,
connected via said communication lines to said television
receivers, for receiving response information from said
television receivers; wherein:

15 said broadcast unit sends retrial information,
according to allowable volume of said communication lines,
included in said data; and

said television receivers retrial-transmit said
response information on basis of said retrial information
received when communications could not be established
with said response information receiving equipment.

20

4. A television receiver for receiving data
broadcast from a broadcast unit and displaying images,
and transmitting response information to response
information receiving equipment over communication lines,

25 wherein:

000149 T5854560

5 said response information is retrieval-
transmitted to said response information receiving
equipment, on basis of retrieval information received from
said broadcast unit, when communications could not be
established with said response information receiving
equipment.

5. A television receiver comprising:

10 means for receiving data sent from a broadcast
unit;

 means for outputting display data based on said
received data to display means; and

15 communication means, being means that transmit
said response information over communication lines, for
retrieval-transmitting said response information, on basis
of retrieval information contained in said received data,
when communications could not be established with said
response information receiving equipment.

20 6. A television receiver comprising:

 means for receiving data sent from a broadcast
unit;

 means for displaying display data based on said
received data; and

25 communication means, being means that transmit
response information over communication lines, for

retrial-transmitting said response information, on basis of retrial information sent from said broadcast unit, when communications could not be established with response information receiving equipment.

5

7. The television receiver according to claim 4, wherein initial transmission scheduling times with said response information receiving equipment are specified by random computation based on received delay information.

10

8. The television receiver according to claim 4, wherein determination as to whether or not to make retrial transmissions is based on a transmission end time sent from said broadcast unit.

15

9. The television receiver according to claim 4, comprising detection means for detecting causes of non-establishment of communications with said response information receiving equipment.

20

10. The television receiver according to claim 9, comprising retrial condition alteration means for altering conditions for retrial transmissions from next time on, on basis of said cause detected.

25

11. The television receiver according to claim 10, wherein said retrial condition alteration means generate notification data for altering setting time width for retrial transmissions.

5

12. The television receiver according to claim 10, wherein said retrial condition alteration means suspend retrial transmissions.

10

13. The television receiver according to claim 9, wherein notification data are generated for making notification of said detected cause.

15

14. The television receiver according to claim 4, wherein time remaining for transmission is computed from a transmission end time sent from said broadcast unit, and said retrial transmission conditions are altered according to said time remaining for transmission.

20

15. The television receiver according to claim 4, wherein notification data are generated for making notification of results of communications with said response information receiving equipment.

25

16. The television receiver according to claim 15, wherein communication results are received from said

17. The television receiver according to claim 15, wherein a history of communications with said response information receiving equipment is stored in memory, and notification data are generated.

15 19. The television receiver according to claim 18,
comprising editing means for editing said response
information when an edit instruction is sent from a user.

communication means for sending response
information over communication lines; wherein:

85

could not be established with response information receiving equipment.

21. The data receiver according to claim 20,
5 wherein said communication means comprise: retrieval time specifying data computation means for computing retrieval time specifying data for specifying retrieval times, on basis of said retrieval information, when communications with said response information receiving equipment could
10 not be established; and transmission means for retransmitting said stored response information when said retrieval time is reached.

22. The data receiver according to claim 20,
15 wherein initial transmission scheduling times with said response information receiving equipment are specified after being randomly computed on basis of received delay information.

20 23. The data receiver according to claim 20, wherein determination as to whether or not to make retrieval transmission is made on basis of transmission end time provided by said broadcast unit.

25 24. The data receiver according to claim 20, comprising detection means for detecting causes of non-

5 data are sent from a broadcast station to a
plurality of data receivers by broadcasting;

response information is sent after a delay from said plurality of data receivers to response information receiving equipment by communication lines;

said data receiver resends said response
information based on said retrial information when
communications could not be established with said
15 response information receiving equipment; and

26. A television receiver comprising:

25 a transport decoder for selecting display data
of a desired service from said selected transport stream;

a control input unit wherewith a user inputs
response information;

a CPU; and

10 said control program retrieval-transmits said
response information via said line communication unit,
based on retrieval information contained in said data, when
communications could not be established with said
response information receiving equipment.

27. A data transceiving system comprising:

a plurality of computers capable of being

```

        said server, when said computers send download
requests to said server, send data specified by said
download requests to said computers;

```

88

programs to said computers making those download requests; and

said computers send download requests, after a delay, to said server, based on said download request
5 transmission-delaying program.

28. A data transceiving system server which, being a server connected to a plurality of computers, upon receiving a download request from any computer, does not
10 cause data specified by that download request to be transmitted to said computer making that download request, but rather sends thereto a download request transmission-delaying program which sends download requests to said server after a delay.

15

29. A data transceiving system comprising:

a broadcast unit for broadcasting data:

a plurality of data receivers for receiving said data and transmitting response information over
20 communication lines; and

response information receiving equipment connected to said data receivers via said communication lines for receiving response information from said data receivers; wherein:

000140" 0941000
said broadcast unit sends probability variation data, included in said data, wherewith probability of generating a transmission time varies over time; and

5 said data receivers determine transmission scheduling times for transmitting to said response information receiving equipment on basis of said received probability variation data.

30. A data transceiving system for transmitting
10 data by broadcast from a broadcast station to a plurality of data receivers, and transmitting response information from said data receivers to response information receiving equipment by communication lines, wherein:

15 said receivers, upon receiving probability variation data wherewith the probability wherewith transmission times are generated varies over time from said broadcast station, determine transmission scheduling times for transmitting to said response information receiving equipment on basis of said received probability
20 variation data.

31. A data receiver for receiving data broadcast from a broadcast unit and sending response information over a communication line to response information
25 receiving equipment, wherein:

transmission scheduling times for transmitting
to said response information receiving equipment are
determined on basis of received probability variation
data, when said probability variation data, wherewith
5 probability with which transmission times are generated
varies over time, are received from said broadcast unit.

32. The data receiver according to claim 31,
wherein time until said transmission scheduling time is
10 random-number generated using said received probability
variation data, and said transmission scheduling time is
determined, when a transmission start enabled time is
received from said broadcast unit.

33. A data transceiving method for receiving
15 broadcast data and sending response information over
communication lines, wherein:

when data inclusive of retrial information
according to allowable volume on said communication lines
20 are received, when communication could not be established
using said communication lines, said response information
are retrial-transmitted on basis of said received retrial
information.

34. A data transceiving method for sending response information over communication lines when data broadcast are received, wherein:

said data include probability variation data
5 wherewith probability of generating a transmission time varies over time; and

transmission scheduling times for transmitting over said communication lines are determined on basis of said received probability variation data.

10 35. A recording medium for storing a program, wherein:

said program is for controlling, by computer, a television receiver that receives data broadcast from a
15 broadcast unit and sends response information to response information receiving equipment over a communication line; and

said program performs processing for retrieval-transmitting said response information to said response
20 information receiving equipment on basis of retrieval information received from said broadcast unit, when communications could not be established with said response information receiving equipment.

25 36. A recording medium for storing a program, wherein:

said program is for controlling, by computer, a data receiver that receives data broadcast from a broadcast unit and sends response information to response information receiving equipment over a communication
5 line; and

said program performs processing for determining transmission scheduling times for transmitting to said response information receiving equipment on bases of received probability variation data, when said
10 probability variation data, wherewith probability of generating a transmission time varies over time, are received.

ABSTRACT OF THE DISCLOSURE

An object is to perform retrieval processing according to the allowable volume on communication lines made available at response information receiving equipment. A broadcast unit 140, when broadcasting video and audio, includes retrieval information in that broadcast, according to the allowable volume on the communication lines between the television receivers and the response information receiving equipment 150. Television receivers effect display based on the received digital data. Response information input by users is sent to the response information receiving equipment 150. The television receivers make retrieval transmissions based on the received retrieval information when communications could not be established with the response information receiving equipment 150. This retrieval information is responsive to the allowable volume on the communication lines between the television receivers and the response information receiving equipment 150, wherefore retrieval transmissions are made according to the allowable volume on the communication lines.

FIG.1




FIG.2





FIG.3

DATA PACKETING



000140" T5857560

FIG.4

PACKETED DATA CONFIGURATION

P I D	CONTENT DATA
-------	--------------

FIG.5

PMT1 (P I D=0X11)

VIDEO		AUDIO	
PID OF ECM	PID OF ES	PID OF ECM	PID OF ES
0X21	0X22	0X21	0X24

FIG.6

PAT (P I D=0X00)


SERVICE	PID OF PMT	PID OF NIT
SV11	0X0011	0X18
SV12	0X0012	
SV13	0X0013	
SV14	0X0014	

FIG.7

NIT (PID=0X18)

TS	TRANSMISSION SPECIFICATION	SERVICE LIST
TS1	f 1	SV11、SV12、SV13、SV14
TS2	f 2	SV21、SV22、SV23、SV24
⋮	⋮	⋮

FIG.8



0954551-041000

FIG. 9




FIG.10




FIG.11




FIG.12

PMT1 (PID=0X0011)

	PID OF ES	PID OF ECM	
VIDEO	0X0096	0X0082	ES (V) 11
	0X0097	0X0082	ES (V) 12
AUDIO	0X0098	0X0082	ES (A) 11
	0X0099	0X0082	ES (A) 12
NAVIGATION DATA	0X0092	0X0082	NVT1
	0X0093	0X0082	NVT2

ENTRY CONTENTS

VIDEO	AUDIO	NAVIGATION DATA
0X0096	0X0098	0X0092

ES (V) 11 ES (A) 11 NVT1

FIG.13

PAT (PID=0X0000)

SERVICE	PID OF PMT
SV11	0X0011
SV12	0X0012
SV13	0X0013
SV14	0X0014

FIG.14

OBJECT TABLE

INDEX	TYPE	X	Y	HANDLER	NORMAL STATUS	FOCUS STATUS
0	BUTTON	500	200	0	0	1
1	BUTTON	500	400	1	2	3

HANDLER DEFINITION TABLE

INDEX	INSTRUCTION (SCRIPT)
0	regist_delayed_connection (001; 06-6361-XXXX; A-395; 1999, 1, 10, 12:00:00; 02:00:00; 1999, 1, 10, 15:00:00; 00:05:00)
1	goto_contents(Index1)

HYPERLINK TABLE

INDEX	VIDEO	AUDIO	NAVIGATION DATA
0	0X0096	0X0098	0X0092
1	0X0097	0X0099	0X0093

BIT MAP TABLE

INDEX	DATA (BIT MAP DATA)
0	MAKE APPLICATION TO CENTER
1	MAKE APPLICATION TO CENTER
2	TO APPAREL SHOP
3	TO APPAREL SHOP

FIG.15

OBJECT TABLE

INDEX	TYPE	X	Y	HANDLER	NORMAL STATUS	FOCUS STATUS
0	BUTTON	500	200	0	0	1
1	BUTTON	500	400	1	2	3

HYPERLINK TABLE

INDEX	VIDEO	AUDIO	NAVIGATION DATA
0	0X0096	0X0098	0X0092
1	0X0097	0X0099	0X0093

HANDLER DEFINITION TABLE

INDEX	INSTRUCTION (SCRIPT)
0	regist_delayed_connection (007; 06-6900-XXXX; A-133; 1999, 1, 10, 13:00:00; 00:30:00; 1999, 1, 10, 16:00:00; 00:10:00)
1	goto_contents (Index0)

BIT MAP TABLE

INDEX	DATA (BIT MAP DATA)
0	MAKE APPLICATION TO CENTER
1	MAKE APPLICATION TO CENTER
2	TO HOUSEHOLD PRODUCT SHOP
3	TO HOUSEHOLD PRODUCT SHOP

FIG.16




FIG.17




FIG.18





FIG.19



0001-01-10 15:55:55

FIG.20




FIG.22




FIG.23




FIG.24

ORDER REGISTRATION NUMBER	t e l	PRODUCT CODE	TRANSMISSION SCHEDULING TIME	SERVICE END TIME	RETRIAL PERIOD
001	06-6361-XXXX	A-395	1999/1/10 13:52:00	1999/1/10 15:00:00	5 MINUTES
007	06-6900-XXXX	B-133	1999/1/10 13:30:00	1999/1/10 16:00:00	10 MINUTES

FIG.25





FIG.26



000740" T5254560

FIG.27

ORDER REGISTRATION NUMBER	DATE	TELEPHONE NUMBER	PRODUCT CODE	HISTORY
001	1999/1/10	06-6361-XXXX	A-395	13:52 BUSY
				13:57 BUSY
007	1999/1/10	06-6900-XXXX	B-133	14:12 SUCCESSFUL
				13:30 BUSY
				13:40 BUSY
				16:00 TIMEOUT

000742" 1525450

FIG.28A




FIG.28B




FIG.28C




FIG.29A




FIG.29B




FIG.29C




FIG.30

STILL IMAGE ES





FIG.31



Declaration and Power of Attorney For Patent Application**特許出願宣言書及び委任状****Japanese Language Declaration****日本語宣言書**

下記の氏名の発明者として、私は以下の通り宣言します。

As a below named inventor, I hereby declare that:

私の住所、私書箱、国籍は下記の私の氏名の後に記載された通りです。

My residence, post office address and citizenship are as stated next to my name.

下記の名称の発明に関して請求範囲に記載され、特許出願している発明内容について、私が最初かつ唯一の発明者（下記の氏名が一つの場合）もしくは最初かつ共同発明者であると（下記の名称が複数の場合）信じています。

I believe I am the original, first and sole inventor (if only one name is listed below) or and original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

DATA TRANSCIVING SYSTEM AND

METHOD THEREFOR

上記発明の明細書（下記の欄で×印がついていない場合は、本書に添付）は、

the specification of which is attached hereto unless the following box is checked:

☐ 月 日に提出され、米国出願番号または特許協力条約国際出願番号を _____ とし、
(該当する場合) _____ に訂正されました。

☐ was filed on _____
as United States Application Number or
PCT international Application Number
_____ and was amended on
_____ (if applicable).

私は、特許請求範囲を含む上記訂正後の明細書を検討し、内容を理解していることをここに表明します。

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

私は、連邦規則法典第37編第1条56項に定義されるとおり、特許資格の有無について重要な情報を開示する義務があることを認めます。

I acknowledge the duty to disclose information which is material to patentability, as defined in Title 37, Code of Federal Regulations, Section 1.56.

Japanese Language Declaration (日本語宣言書)

私は、米国法典第35編119条(a)-(d)項または365条(b)項に基づき下記の、米国以外の国の少なくとも一カ国を指定している特許協力条約365(a)項に基づく国際出願、又は外国での特許出願もしくは発明者証の出願についての外国優先権をここに主張するとともに、優先権を主張している、本出願の前に出願された特許又は発明者証の外国出願を以下に、枠内をチェックすることで、示しています。

I hereby claim foreign priority under Title 35, United States Code, Section 119(a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT international application which designated at least one country other than the United States, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or PCT international application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application(s)

外国での先行出願

Hei 11-103619(P)

(103619/1999)

(Number)

(番号)

JAPAN

(Country)

(国名)

12/04/1999

(Day/Month/Year Filed)

(出願年月日)

Priority Not Claimed

優先権主張なし



(Number)

(番号)

(Country)

(国名)

(Day/Month/Year Filed)

(出願年月日)



私は、第35編米国法典119条(e)項に基づいて下記の米国特許出願規定に記載された権利をここに主張いたします。

I hereby claim the benefit under Title 35, United States Code, Section 119(e) of any United States provisional application(s) listed below.

(Application No.)

(出願番号)

(Filing Date)

(出願日)

(Application No.)

(出願番号)

(Filing Date)

(出願日)

私は、下記の米国法典第35編120条に基づいて下記の米国特許出願に記載された権利、又は米国を指定している特許協力条約365条(c)に基づく権利をここに主張します。また、本出願の各請求範囲の内容が米国法典第35編112条第1項又は特許協力条約で規定された方法で先行する米国特許出願に開示されていない限り、その先行米国出願書提出日以降で本出願書の日本国内または特許協力条約国際提出日までの期間中に入手された、連邦規則法典第37編1条56項で定義された特許資格の有無に関する重要な情報について開示義務があることを認識しています。

I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States application(s), or 365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Code Section 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of application.

(Application No.)

(出願番号)

(Filing Date)

(出願日)

(Status: Patented, Pending, Abandoned)

(現況: 特許許可済、係属中、放棄済み)

(Application No.)

(出願番号)

(Filing Date)

(出願日)

(Status: Patented, Pending, Abandoned)

(現況: 特許許可済、係属中、放棄済み)

私は、私自身の知識に基づいて本宣言書中で私が行う表明が真実であり、かつ私の入手した情報と私の信じるに基づく表明が全て真実であると信じていること、さらに故意になされた虚偽の表明及びそれと同等の行為は米国法典第18編第1001条に基づき、罰金または拘禁、もしくはその両方により処罰されること、そしてそのような故意による虚偽の声明を行えば、出願した、又は既に許可された特許の有効性が失われることを認識し、よってここに上記のごとく宣誓を致します。

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Japanese Language Declaration (日本語宣言書)

委任状： 私は下記の発明者として、本出願に関する一切の手続を米国特許商標局に対して遂行する弁理士または代理人として、下記の者を指名いたします（弁護士、または代理人の氏名及び登録番号を明記のこと）。

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith (list name and registration number)

Daniel W. Sixbey, (Reg. No. 20,932)
Gerald J. Ferguson, Jr. (Reg. No. 23,016)
Joan K. Lawrence (Reg. No. 29,940)
Evan R. Smith (Reg. No. 35,683)

Stuart J. Friedman (Reg. No. 24,312)
David S. Safran (Reg. No. 27,997)
Donald R. Studebaker (Reg. No. 32,815)
Tim L. Brackett (Reg. No. 36,092)

Charles M. Leedom, Jr. (Reg. No. 26,477)
Thomas W. Cole (Reg. No. 28,290)
Jeffrey L. Costellia (Reg. No. 35,483)
Eric J. Robinson (Reg. No. 38,285)

書類の送付先：

Send Correspondence to:

Mr. Donald R. Studebaker
NIXSON PEABODY LLP
ATTORNEY AT LAW
8180 Greensboro Drive
Suite 800
McLean, Virginia 22102
U.S.A.

Mr. Donald R. Studebaker
NIXSON PEABODY LLP
ATTORNEY AT LAW
8180 Greensboro Drive
Suite 800
McLean, Virginia 22102
U.S.A.

直通電話連絡先：（名称および電話番号）

Direct Telephone Calls to: (name and telephone number)

Mr. Donald R. Studebaker
(703) 790-9110

Mr. Donald R. Studebaker
(703) 790-9110

唯一のまたは第一の発明者の氏名	Full name of sole or first inventor Yasuyuki SONODA		
同発明者の署名	日付	Inventor's signature <i>Yasuyuki Sonoda</i>	Date March 24, 2000
住所	Residence Kyoto-shi, Kyoto, JAPAN		
国籍	Citizenship JAPAN		
郵便の宛先	Post Office address 22-1, Shinomiyaiwakubotyou, Yamasinaku, Kyoto-shi, Kyoto 607-8028, JAPAN		
第二の共同発明者の氏名（該当する場合）	Full name of second joint inventor, if any Tatsuya SHIMOJI		
同第二発明者の署名	日付	Second Inventor's signature <i>Tatsuya Shimoji</i>	Date March 24, 2000
住所	Residence Neyagawa-shi, Osaka, JAPAN		
国籍	Citizenship JAPAN		
郵便の宛先	Post Office Address 30-3-1102, Miiminamimati, Neyagawa-shi, Osaka 572-0019, JAPAN		

（第三またはそれ以降の共同発明者に対しても同様に記載し、署名をすること。）

(Supply similar information and signature for third and subsequent joint inventors.)

Japanese Language Declaration (日本語宣言書)

委任状： 私は下記の発明者として、本出願に関する一切の手続を米国特許商標局に対して遂行する弁理士または代理人として、下記の者を指名いたします（弁護士、または代理人の氏名及び登録番号を明記のこと）。

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith (*list name and registration number*)

Daniel W. Sixbey, (Reg. No. 20,932)
Gerald J. Ferguson, Jr. (Reg. No. 23,016)
Joan K. Lawrence (Reg. No. 29,940)
Evan R. Smith (Reg. No. 35,683)

Stuart J. Friedman (Reg. No. 24,312)
David S. Safran (Reg. No. 27,997)
Donald R. Studebaker (Reg. No. 32,815)
Tim L. Brackett (Reg. No. 36,092)

Charles M. Leedom, Jr. (Reg. No. 26,477)
Thomas W. Cole (Reg. No. 28,290)
Jeffrey L. Costellia (Reg. No. 35,483)
Eric J. Robinson (Reg. No. 38,285)

書類の送付先：

Send Correspondence to:

Mr. Donald R. Studebaker
NIXSON PEABODY LLP
ATTORNEY AT LAW
8180 Greensboro Drive
Suite 800
McLean, Virginia 22102
U.S.A.

Mr. Donald R. Studebaker
NIXSON PEABODY LLP
ATTORNEY AT LAW
8180 Greensboro Drive
Suite 800
McLean, Virginia 22102
U.S.A.

直通電話連絡先：（名称および電話番号）

Direct Telephone Calls to: (*name and telephone number*)

Mr. Donald R. Studebaker
(703) 790-9110

Mr. Donald R. Studebaker
(703) 790-9110

第三の共同発明者の氏名（該当する場合）		Full name of third joint inventor, if any	
		Kazuo OKAMURA	
同第三発明者の署名	日付	Third Inventor's signature	Date
		<i>Kazuo Okamura</i>	March 24, 2000
住所		Residence	
		Hirakata-shi, Osaka, JAPAN	
国籍		Citizenship	
		JAPAN	
郵便の宛先		Post Office address	
		4-5-8-302, Hoshigaoka, Hirakata-shi, Osaka 573-0013, JAPAN	
第四の共同発明者の氏名（該当する場合）		Full name of fourth joint inventor, if any	
同第四発明者の署名	日付	Fourth Inventor's signature	Date
住所		Residence	
国籍		Citizenship	
郵便の宛先		Post Office Address	